MATERIAL SAFETY DATA SHEET

NAPALINE BLUEHAZARD RATINGS (0-4)DATE: 9/7/05FIRE 2REACTIVITY 0SUPERSEDES: 9/27/04TOXICITY 2SPECIAL

SUPPLIER: Suede Products

18600 Graphics Court Tinley Park, IL 60477 EMERGENCY PHONE (708) 614-0939 INFOTRAC: (800) 535-5053

TRADE NAME: Napaline Blue PRODUCT TYPE: Suede dye CHEMICAL FORMULA: Mixture CHEMICAL NAME: N/A

COMPONENT LIST - SECTION I

CAS TLV TLV **ACGIH COMPONENT** REG# **OSHA** <u>%</u> 30 - 40 200 ppm Alcohol Blend Mixture 200 ppm Blue Pigment Dispersion Mixture 10 - 20 N/A N/A

This product contains no ingredients that are listed in the SARAIII, Section 313 Inventory.

PHYSICAL PROPERTIES - SECTION II

APPEARANCE: Aqueous blue liquid with solvent odor

pH: N/D
VISCOSITY: <10 cps
FREEZING POINT: N/D
BOILING POINT: N/D
VAPOR PRESSURE: N/D
VAPOR DENSITY: <1

SOLUBILITY IN WATER: Substantial VOLATILE (% WT): Approx. 95 SPECIFIC GRAVITY: 0.99 EVAPORATION RATE: < 1

FIRE AND EXPLOSION HAZARD - SECTION III

FLASH POINT: 78 F

LOWER EXPLOSION LIMIT: N/D UPPER EXPLOSION LIMIT: N/D

AUTO IGNITION TEMP: N/D

EXTINGUISHING MEDIUM: Foam, alcohol foam, CO₂, dry chemical, water spray

SPECIAL FIRE FIGHTING PROCEDURES:

Cool and use caution when approaching fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Container may burst in heat of fire. Product contains water so may not support combustion.

HEALTH HAZARDS - SECTION IV

THRESHOLD LIMIT VALUES: None established.

PRIMARY ROUTES OF EXPOSURE: Eye, skin, inhalation.

CARCINOGENS OR SUSPECTED CARCINOGENIC INGREDIENTS: None

EFFECTS OF OVEREXPOSURE:

IF IN EYES - Direct contact can cause irritation.

IF ON SKIN - Prolonged or repeated contact may cause irritation.

IF INHALED - Spray mist may cause irritation to nose, throat and lungs.

IF SWALLOWED - May cause nausea, vomiting and abdominal pain.

NAPALINE BLUE - PAGE 2

EMERGENCY AND FIRST AID PROCEDURES:

IF IN EYES: Immediately flush eyes with clear water for <u>at least 15 minutes</u>, occasionally lifting lower and upper lids. If irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water.

IF SWALLOWED: Drink large amount of water or milk and seek medical attention. Do not give anything by mouth to an unconscious person.

IF INHALED: If mist causes discomfort, leave area and move to fresh air.

REACTIVITY - SECTION V

STABILITY: Stable

CONDITIONS TO AVOID: Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield oxides of carbon.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bleach.

SPILLS OR LEAK PROCEDURE - SECTION VI

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Rinse area thoroughly with water.

WASTE DISPOSAL METHODS:

For undiluted product: Disposal is regulated under RCRA as ignitable waste. Waste from normal product use may be sewered in compliance with federal, state and local regulations.

SPECIAL PROTECTION - SECTION VII

VENTILATION TYPE: General room ventilation is normally adequate. RESPIRATORY PROTECTION: Not required under normal use conditions.

PROTECTIVE GLOVES: Impervious.

EYE PROTECTION: Safety glasses if splashing likely.

OTHER PROTECTIVE EQUIPMENT:

STORAGE AND HANDLING - SECTION VIII

Keep from freezing. Do not weld, heat or drill on or near container.

SHIPPING - SECTION IX

PROPER SHIPPING NAME: Paint Related Material U.S. DOT HAZARD CLASS: 3, UN1263, PG III

LABEL REQUIREMENTS: Flammable

MISCELLANEOUS - SECTION X

ABBREVIATIONS: N/A: Not applicable UNK: Unknown

N/D: Not determined <: Less than N/E: Not established >: Greater than

PREPARED BY: JOHN ROTH